CONNECTIVITY

Data sheet: CN-127

Product code	:	CN-127
Product name	:	IRDA Keyboard switch to PDA
EAN code	:	8716502005550
Qty. masterpack / carton	:	5/20

Product weight	:	51 gr.
Product dimensions	:	55 (W) x 66 (D) x 24 mm (H)
Gift box weight	:	150 gr.
Gift box dimensions	:	209 (W) x 145,5 (D) x 45 mm (H)
Masterpack weight	:	2100 gr.
Masterpack dimensions	:	240 (W) x 230 (D) x 170 mm (H)
Carton weight	:	9,5 Kg.
Carton dimensions	:	47 (W) x 35 (D) x 26,5 cm (H)

This IrDA Keyboard Switch enables you to use your existing PS/2 keyboard both for your PC and for your PDA (with infrared device). By placing the Keyboard Switch between your keyboard and your PC, you will be able to switch between your PC and a wireless infrared connection with your PDA simply by pressing a button. This makes it a good deal easier to process appointments and enter data into your PDA.

Box content:

- IrDA Keyboard Switch
- PS/2 Y cable
- PS/2 extension cable
- 3 x AAA batteries
- CD-ROM
- Quick Installation Guide

System requirements:

- Windows CE 3.0 (Pocket PC 2000, 2002 and 2003)
- Palm OS 5.0 or higher

CONNECTIVITY

Data sheet: CN-127

Key features:

- Use the Standard PS/2 keyboard to operate between PC and PDA
- Infrared wireless connectivity, no needs to connect any connector to PDA
- Keyboard data input under PC or PDA switch-able
- Built in LED for PC or PDA mode, and low battery power indication
- Easy and comfortable operate and data input via the full-sized keyboard
- Battery operation in PDA mode, and no needs extra power while operate in PC mode
- Low power consumption- Only 3 AAA Alkaline batteries, could continue keyboard key-in with no any interrupt more than two days.
- Fully compatible with the Palm and Windows CE, Palm OS driver up gradable.

Technical specifications:

- Compatibility: Windows CE and Palm O.S. 5.0 or higher based PDA
- IR communication distance: 0 to 20cm
- IR communication angle: 30 degrees corn angle
- Connection: 1 mini DIN6 female connector to PS/2 keyboard
- 1 mini DIN6 male connector to PC keyboard port
- 1 15-pin PCMCIA connector to IR-620K
- Power source: DC 4.5V
- Power consumption: Active current < 20mA, Standby current 5mA
- Dimension/Weight: 67.5mmL x 56.4mmW x 27mmH/ 105g (Include Y cable)
- Operating/ Storage Temperature: 0 to 60° / -20 to 80°